



CB1300 SERIES

3/8" WIRE ROPE



NOTES

1. ALL DIMENSIONS ARE IN INCHES. INTERPRET PER ANSI Y14
2. ALL DIMENSIONS ARE NOMINAL AND FOR REFERENCE ONLY

ISOLATOR PART NO.	NOMINAL H (in)	NOMINAL W (in)	LOAD MODE	SHOCK AVERAGE K (lb/in)	VIBRATION AVERAGE K (lb/in)	MAX. RATED DYNAMIC TRAVEL (lb/in)
CB1300-12-[]	2.69	3.13	COMPRESSION	2270	1625	0.90
			SHEAR/ROLL	620	595	1.00
			45 DEG. C/R	695	2010	1.40
CB1300-15-[]	2.80	3.31	COMPRESSION	1310	3395	1.00
			SHEAR/ROLL	555	550	1.20
			45 DEG. C/R	625	1860	1.60
CB1300-17-[]	2.90	3.40	COMPRESSION	1005	2445	1.20
			SHEAR/ROLL	420	445	1.40
			45 DEG. C/R	470	1555	2.00
CB1300-20-[]	2.90	3.50	COMPRESSION	655	1315	1.40
			SHEAR/ROLL	300	345	1.60
			45 DEG. C/R	310	1010	2.40
CB1300-25-[]	3.25	4.25	COMPRESSION	520	1030	1.60
			SHEAR/ROLL	235	270	1.80
			45 DEG. C/R	240	815	2.80
CB1300-30-[]	3.00	4.13	COMPRESSION	655	1315	1.40
			SHEAR/ROLL	300	345	1.60
			45 DEG. C/R	310	1010	2.40
CB1300-35-[]	3.50	4.25	COMPRESSION	415	775	1.80
			SHEAR/ROLL	175	215	2.00
			45 DEG. C/R	190	545	3.20
CB1300-40-[]	4.13	4.75	COMPRESSION	300	600	2.20
			SHEAR/ROLL	130	140	2.40
			45 DEG. C/R	125	420	4.00
CB1300-50-[]	4.25	5.50	COMPRESSION	200	355	2.40
			SHEAR/ROLL	100	110	2.60
			45 DEG. C/R	85	300	4.40
CB1300-60-[]	4.88	6.13	COMPRESSION	150	215	2.80
			SHEAR/ROLL	65	90	3.00
			45 DEG. C/R	55	190	4.80
CB1300-70-[]	6.00	7.50	COMPRESSION	90	110	4.40
			SHEAR/ROLL	30	70	3.60
			45 DEG. C/R	30	65	5.20



JOB NAME:

CUSTOMER :

CUSTOMER P.O.:

SALES ORDER:

MODEL CB1300 SERIES WIRE ROPE ISOLATOR



VMC GROUP
CONTROLLED ENVIRONMENT SOLUTIONS™

Bloomington, NJ Houston, TX Corona, CA Wind Gap, PA

DRAWING NO.:

REVISION:

SHEET:

SCALE :

1 OF 2

NONE

CB [] 1300 [] - 30 [] - C2

MOUNTING HOLE OPTIONS

OF COILS (BLANK = 6 COILS)

FAMILY SERIES SIZE (-10 THRU -60)

SPECIAL REQUIREMENTS (D*, R, F, J**)

FAMILY SERIES

WIRE ROPE REQUIREMENTS

BLANK = 302 STAINLESS STEEL (STANDARD), OR G, OR S

OF COILS (PATTERN OR PROFILE TO MATCH)

FAMILY NAME

SPECIAL REQUIREMENTS

D	DFARS*
F	THREAD FREE CABLE
G	GALVANIZED CABLE
J	ALT STYLE CONSTRUCTION**
M	METRIC INSERTS
R	RoHS
S	STAINLESS STEEL TOTAL

* DFARS COMPLIANT RAW MATERIAL COMES FROM A LIMITED GROUP OF APPROVED SUPPLIERS AND IS NOT REQUIRED ON STANDARD PARTS.

** SUBJECT TO MANUFACTURER'S DISCRETION. CONTACT VMC FOR APPLICABILITY.

FEATURES & BENEFITS:

- WIDE RANGE OF AVAILABLE SIZES PERMITS ATTACHMENT TO ALMOST ANY MACHINERY OR ENCLOSURE REGARDLESS OF WEIGHT.
- COMPACT, LOW-PROFILE DESIGN AND THE ABILITY TO ATTENUATE HEAVY SHOCK LOADS WITH MINIMUM DEFLECTION ALLOWS USE WHERE SPACE IS AT A PREMIUM.
- THREE-PLANE, ALL-AXIS ISOLATION MEANS THAT EQUIPMENT IS FREE TO MOVE IN ANY DIRECTION - VERTICALLY, HORIZONTALLY, AND Laterally.
- CUSTOM WINDING, LOOP COUNT AND MOUNTING FEATURES ARE AVAILABLE TO MEET SPECIFIC REQUIREMENTS.
- OPERATING TEMPERATURE RANGE -400F TO +700F.

STANDARD MATERIALS / FINISHES:


- **WIRE ROPE MATERIALS:** SERIES 302 STAINLESS STEEL.
- **BAR MATERIALS:** ALUMINUM ALLOY 6061-T6, -T6510, OR -T6511 PER SAE AMS4113, SAE AMS4150, OR ASTM B221 WITH CHEMICAL CONVERSION COATING PER MIL-DTL-5541, CLASS 1A.

SPECIAL OPTIONS:

- **WIRE ROPE MATERIALS:** GALVANIZED, IMPROVED PLOW WIRE, PLASTIC FILLED VALLEY WIRE, INCONEL 600, STAINLESS STEEL TYPE 316, STAINLESS STEEL TYPE 305.
- **BAR MATERIALS:** STAINLESS STEEL, CRES TYPE 302, 303, 304, OR 304L WITH FINISH PASSIVATED PER QQ-P-35C TYPE II.
- **MOUNTING CONFIGURATIONS:** INSERTS, THREAD TYPES, CLEARANCE HOLES.
- CONTACT VMC FOR OTHER MATERIAL AVAILABILITIES.


MOUNTING HOLE OPTIONS:**M = METRIC** M C'SK = Ø.284 X 90° M INSERT = M6 X 1.0

4X Ø.284 THRU HOLE




4X Ø.284 X C'SK 82°

4X Ø.284 X C'SK 82°




4X Ø.284 X C'SK 82°

4X Ø.284 THRU HOLE




4X INSERT 1/4 - 28

4X INSERT 1/4 - 28




4X Ø.284 X C'SK 82°

4X INSERT 1/4 - 28



4X INSERT 1/4 - 28

4X Ø.284 THRU HOLE



4X Ø.284 THRU HOLE



JOB NAME:

CUSTOMER :

CUSTOMER P.O.:

SALES ORDER:

MODEL CB1300 SERIES
WIRE ROPE ISOLATOR



VMC GROUP
CONTROLLED ENVIRONMENT SOLUTIONS™

Bloomington, NJ Houston, TX Corona, CA Wind Gap, PA

DRAWING NO.:

REVISION:

SHEET:

SCALE :

2 OF 2

NONE