


4 1/2

REV.	DESCRIPTION	DATE	BY

TYPE HRSA-1E PRE-COMPRESSED ELASTOMERIC & SPRING ANGULARITY HANGERS									
FOR 1" NOMINAL DEFLECTION									
HANGER	RATED LOAD	DEFLECTION	SPRING RATE	SPRING	ELEMENT LOAD				
HANGER	(LBS)	(IN)	(LB/IN)	COLOR CODE	& COLOR CODE				
HRSA-1E-195PR	195	2.21	100	DK BLUE	RE-C-380 BLACK				
HRSA-1E-400PR	400	1.70	303	BLACK	RE-C-520 RED				
HRSA-1E-650PR	650	1.44	619	RED	RE-C-840 GREEN				
HRSA-1E-1000PR	1000	1.47	1000	TAN	RE-C-1070 GRAY				
HRSA-1E-1400PR	1400	1.35	1400	PINK	RE-C-2000 BLUE				
HRSA-1E-2000PR	2000	1.61	1802	WHITE	RE-C-2000 BLUE				



NOTES

135R-103812

REV.:3

4/20/20

1. HANGER RODS, NUTS AND WASHERS, AS SHOWN, NOT BY THE VMC GROUP. INSTALL WASHER .165 THK. MIN. X 2-7/8 O.D. MIN. WITH REQUIRED INSIDE DIAMETER TO ACCOMMODATE ROD SIZE IN USE. THIS CAN BE ACCOMPLISHED BY USING A SINGLE WASHER OR BY STACKING NOT MORE THAN TWO WASHERS

SEISMIC VERTICAL LIMIT-STOP, NUT AND WASHER, TIGHTEN

TOGETHER (SEE NOTE 3)

- 2. STANDARD FINISH: HANGER BOX PAINTED, POWDER COATED OR GALVANIZED STEEL, SPRING POWDER COAT.
- 3. SEISMIC VERTICAL-STOP HARDWARE REQUIRED FOR SEISMIC APPLICATIONS.

3/8 OPERATING

GAP

- 4. ALL DIMENSIONS IN INCHES. INTERPRET PER ANSI Y14.
- 5. ALL DIMENSIONS ARE FOR REFERENCE, DIMENSIONS SHOWN AS NOMINAL.
- 6. ALL SPRINGS ARE DESIGNED WITH MINIMUM 50% OVER-TRAVEL.
- 7. HANGER BOXES ARE AVAILABLE PRE-COMPRESSED UP TO THEIR DESIGNATED MAX. LOAD. PERCENTAGE OF PRE-COMPRESSION TO BE DETERMINED BY ENGINEERED APPLICATION OR AS REQUESTED BY CUSTOMER.CONSULT FACTORY FOR POSSIBLE ADDITIONAL PARAMETERS AND OR LIMITATIONS.
- 8. HANGER BOXES WITH AN ELASTOMERIC ELEMENT HAVE UP TO AN ADDITIONAL 1/2" NOMINAL DEFLECTION.
- 9. DOUBLE LOWER NUT PROVIDED.
- 10.ROD EXTENSION BELOW LOWER NUT EXTENDS (1.5XROD DIA.) AS SHIPPED.
- 11.PRE-COMPRESSED 50% OF SPRING RATED DEFLECTION
- 12.RATED DEFLECTIONS ARE WITHIN 25% OF NOMINAL. HIGHER DEFLECTIONS ARE ALLOWED IF THEY MEET SPECIFICATIONS.

ISOLATOR SELECTIONS				
LOC 1:	LOC 2:			
LOC 3:	LOC 4:			
LOC 5:	LOC 6:			
LOC 7:	LOC 8:			
CUSTOMER EQP'T. TAG:				

NOTE: MATERIAL SHOWN IS FOR (1) SET.

OTHER MATERIALS, COMPOUNDS, OR FINISHES WITH EQUAL OR SUPERIOR PROPERTIES MAY BE SUBSTITUTED AS THEY BECOME AVAILABLE.

CERTIFIED FOR:	MODEL HRSA-1E 195-2000 LBS.		SCALE : NONE	Membe.
JOB NAME:	PRE-COMPRESSED		SHEET:	···· ·VISCM A
CUSTOMER:	ELASTOMERIC AND SPRING ANGULARITY	VMC	1 OF 1	
CUSTOMER P.O.:	HANGERS	GROUP THE POWER OF TOGETHER*	DRAWING NO.:	REVISION
SALES ORDER:	1 INCH DEFLECTION	Bloomingdale, NJ 07403 Houston, TX 77041		