

TYPE HRSA-3E ELASTOMERIC & SPRING ANGULARITY HANGERS FOR 3" NOMINAL DEFLECTION DEFLECTION | SPRING RATE **SPRING** ELEMENT COLOR CODE COLOR CODE RE-D-1900-GREEN 3.00 533 DK GRAY 2.53 833 **DK YELLOW** RE-D-3050-GRAY RED 2.44 1000 RE-D-3050-GRAY 2.63 1333 **GREEN** RE-D-4200-BLUE

REV.

DOCUMENT SPECIFICATION ACKNOWLEDGMENT SIGNATURE CERTIFIES DRAWING HAS BEEN REVIEWED AND APPROVED AS ILLUSTRATED. CUSTOMER ACKNOWLEDGMENTS ANY REVISION, CHANGE, OR MODIFICATION MADE TO THIS APPROVAL AFTER IT HAS BEEN SIGNED AND APPROVED MAY AFFECT PRODUCT DELIVERY DATE AND/OR COST. RECEIVED BY: DATE:

DESCRIPTION

DATE

BY



- SEISMIC VERTICAL LIMIT-STOP REQUIRED FOR SEISMIC APPLICATIONS; NOT BY THE VMC GROUP. INSTALL WASHER .25 THK. MIN. X 4 O.D. MIN. WITH REQUIRED INSIDE DIAMETER TO ACCOMMODATE ROD SIZE IN USE. THIS CAN BE ACCOMPLISHED BY USING A SINGLE WASHER OR BY STACKING NOT MORE THAN TWO WASHERS AS SHOWN
- ALL DIMENSIONS ARE FOR REFERENCE; DIMENSIONS SHOWN AS NOMINAL. INTERPRET PER ANSI Y14.
- ALL SPRINGS ARE DESIGNED WITH MINIMUM 50% OVER-TRAVEL.

SALES ORDER:

- HANGER BOXES WITH AN ELASTOMERIC ELEMENT HAVE UP TO AN ADDITIONAL 1/2" NOMINAL DEFLECTION.
- HANGER BOXES ARE AVAILABLE PRE-COMPRESSED UP 50% OF THEIR DESIGNATED MAX. LOADS. 7.
- RATED DEFLECTIONS ARE WITHIN 25% OF NOMINAL. HIGHER DEFLECTIONS ARE ALLOWED IF THEY MEET SPECIFICATIONS.

ISOLATOR SELECTIONS	
LOC 1:	LOC 2:
LOC 3:	LOC 4:
LOC 5:	LOC 6:
LOC 7:	LOC 8:
CUSTOMER EQP'T. TAG:	

NOTE: MATERIAL SHOWN IS FOR (1) SET.

OTHER MATERIALS, COMPOUNDS, OR FINISHES WITH EQUAL OR SUPERIOR PROPERTIES MAY BE SUBSTITUTED AS THEY BECOME AVAILABLE.



CERTIFIED FOR: JOB NAME: CUSTOMER: CUSTOMER P.O.:

MODEL HRSA-3E 1600-3500 LBS. ELASTOMERIC AND SPRING ANGULARITY HANGERS 3 INCH NOMINAL DEFLECTION



Houston, TX 77041

NONE SHEET:

SCALE:

1 OF 1

Bloomingdale, NJ 07403

DRAWING NO.: REVISION