

	TYPE HRSA-3E PRE-COMPRESSED ELASTOMERIC & SPRING ANGULARITY HANGERS FOR 3" NOMINAL DEFLECTION							
	RATED							

TOTAL TROUBING ALE DEL ELECTRON						
HANGER	RATED LOAD (LBS.)	DEFLECTION (IN)	SPRING RATE (LBS/IN)	SPRING COLOR CODE	SPRING COLOR CODE	
HRSA-3E-1600PR	1600	3.00	533	DK. GRAY	RE-D-1900-GREEN	
HRSA-3E-2110PR	2110	2.53	833	DK. YELLOW	RE-D-3050-GRAY	
HRSA-3E-2440PR	2440	2.44	1000	RED	RE-D-3050-GRAY	
HRSA-3E-3500PR	3500	2.63	1333	GREEN	RE-D-4200-BLUE	

DOCUMENT SPECIFICATION ACKNOWLEDGMENT SIGNATURE CERTIFIES DRAWING HAS BEEN REVIEWED AND APPROVED AS ILLUSTRATED. **CUSTOMER ACKNOWLEDGMENTS** ANY REVISION, CHANGE, OR MODIFICATION MADE TO THIS APPROVAL AFTER IT HAS BEEN SIGNED AND APPROVED.

DESCRIPTION

MAY AFFECT PRODUCT DELIVERY DATE AND/OR COST.

RECEIVED BY:



ISOLATOR SELECTIONS				
LOC 1:	LOC 2:			
LOC 3:	LOC 4:			
LOC 5:	LOC 6:			
LOC 7:	LOC 8:			
CUSTOMER EQP'T. TAG:				

NOTE: MATERIAL SHOWN IS FOR (1) SET.



7. PRE-COMPRESSED UP TO THEIR DESIGNATED MAX. LOAD. PERCENTAGE OF PRE-COMPRESSION TO BE DETERMINED BY ENGINEERED APPLICATION OR AS REQUESTED BY CUSTOMER, CONSULT FACTORY FOR POSSIBLE ADDITIONAL PARAMETERS AND OR LIMITATIONS.

1. HANGER RODS, NUTS AND WASHERS, AS SHOWN, NOT BY THE VMC GROUP. INSTALL WASHER .16 THK. MIN. X 2-1/2 O.D. MIN. WITH REQUIRED INSIDE DIAMETER TO ACCOMMODATE ROD SIZE IN USE. THIS CAN BE ACCOMPLISHED BY USING A SINGLE

8. HANGER BOXES WITH AN ELASTOMERIC ELEMENT HAVE UP TO AN ADDITIONAL 1/2" NOMINAL DEFLECTION

3. SEISMIC VERTICAL LIMIT-STOP HARDWARE REQUIRED FOR SEISMIC APPLICATIONS SUPPLIED BY VMC

WASHER OR BY STACKING NOT MORE THAN TWO WASHERS.

6. SPRINGS ARE DESIGNED WITH MINIMUM 50% OVER-TRAVEL.

JOB NAME:

CUSTOMER:

CUSTOMER P.O.:

SALES ORDER:

5. DIMENSIONS ARE FOR REFERENCE, DIMENSIONS SHOWN AS NOMINAL

CERTIFIED FOR:

4. DIMENSIONS IN INCHES. INTERPRET PER ANSI Y14.

9. RATED DEFLECTIONS ARE WITHIN 25% OF NOMINAL. HIGHER DEFLECTIONS ARE ALLOWED IF THEY MEET SPECIFICATIONS.

2. STANDARD FINISH: HANGER BOX - PAINTED. POWDER COATED OR GALVANIZED STEEL. SPRING - POWDER COAT.

NOTES:

MODEL HRSA-3E 1600-3500 LBS. PRE-COMPRESSED **ELASTOMERIC & SPRING ANGULARITY** HANGERS 3 INCH NOMINAL DEFLECTION

	1C GROUP
--	----------

OTHER MATERIALS, COMPOUNDS, OR FINISHES WITH EQUAL OR SUPERIOR

PROPERTIES MAY BE SUBSTITUTED AS THEY BECOME AVAILABLE

Bloomingdale, NJ Houston, TX Wind Gap, PA SCALE: SHEET: DRAWING NO.: REVISION NONE 1 of 1