-BASE DIMENSION (WIDTH)-ISOLATOR -ISOLATOR PUMP END BASE DIMENSION (LENGTH) ISOLATOR ISOLATOR -REINFORCING -CORNER STEEL CONNECTOR ANCHOR BOLT TEMPLATE-MOTOR END TBD (MIN. OF 13") -BRACKET ISOLATOR TBD-6 REQ'D **ISOLATOR** TBD-**ISOLATOR** -CLEARANCE OVERALL HEIGHT

REV.	DESCRIPTION	DATE	BY

	ISOLATORS								
		_ATOR YPE	COLO	DR	RATED LOAD (Ibs.)	RATED DEFL (in.)			
1									
2									
3									
4									
5									
6									
EQUIPMEN	EQUIPMENT / MODEL:								
CUST REF DWG:									
MOTOR									
FRAME SIZE:		HP	RPM		WT.				
PUMP									
SUCTION		DISCHARGE			WT.				
CONCRETE					WT.				
	WT.								
TOTAL ESTIMATED SHIPPING WEIGHT:									

TAG No.

QTY. REQ'D. \_\_\_\_\_

## NOTES:

CERTIFIED FOR.

CUSTOMER P.O.:

SALES ORDER:

211R-105122

REV.:1 1/14/21

RATED DEFLECTIONS ARE WITHIN 25% OF NOMINAL. HIGHER DEFLECTIONS ARE ALLOWED IF THEY MEET SPECIFICATIONS.

OTHER MATERIALS, COMPOUNDS, OR FINISHES WITH EQUAL OR SUPERIOR PROPERTIES MAY BE SUBSTITUTED AS THEY BECOME AVAILABLE. SCALE:

CERTIFIED FOR.		
JOB NAME:		
CUSTOMER :		

MODEL MPF 6 INCH SEISMIC MODULAR POURING FORM INERTIA BASE "T" SHAPE 2 INCH DEFLECTION

-HOUSEKEEPING PAD



Houston, TX 77041

SHEET: 1 OF 1

NONE

DRAWING NO.: REVISION